

## TECHNICAL SPECIFICATIONS

<b>Model:</b>	Type B, Type D
<b>Weapon type:</b>	Semi-automatic pistol, striker-fired
<b>Caliber:</b>	9 mm Luger
<b>Locking System:</b>	Recoil operated, with vertical locking block – AF-Speedlock™
<b>Length (overall):</b>	Standard Barrel 196 mm (7,7") Threaded Barrel 214 mm (8,4")
<b>Height (overall):</b>	132.6 mm (5.2")
<b>Width (overall):</b>	36.1 mm (1,4")
<b>Weight (with empty magazine):</b>	840 g (29,6 oz.)
<b>Distance Hand-Barrel Axis:</b>	12 mm
<b>Barrel length:</b>	- 109 mm (4,3"), for the standard barrel - 127 mm (5"), for the threaded barrel
<b>Threaded barrel options:</b>	½-28"; 13,5×1 LH
<b>Barrel Rifling:</b>	1:10RH, 6 grooves
<b>Barrel Crown:</b>	45DEG
<b>Magazine capacity:</b>	16 cartridges, double stack (compact magazine body) 19 cartridges, double stack (long magazine body)
<b>Trigger:</b>	Single action, pre-cocked
<b>Trigger Pull:</b>	5 LBS.
<b>Safety:</b>	Trigger safety, firing pin safety
<b>Sights:</b>	Fixed, replaceable
<b>Sight Radius:</b>	165 mm (6.5")
<b>Front Sight Height:</b>	5.2-7.6 mm (.205-.300") 1-9 graduation for adjusting; 1.6mm (.063") from top to center of fiber optic
<b>Front Sight Width:</b>	3.2 mm (.126")
<b>Rear Sight Width:</b>	18 mm (.708")
<b>Rear Sight U Notch Width:</b>	3.2 mm (.126") square
<b>Optic Footprint Options:</b>	Shield Footprint + Cover Plate, Aimpoint Acro P2
<b>Materials:</b>	Steel (slide, barrel, frame), polymer (pistol grip)
<b>Accessory Rail:</b>	Piccatiny